



CE EN 62368-1

Features:

- Universal AC input / Full range
- Refer to medical safety EN60601-1(2XMOPP)
- Protections: Short circuit /Over load /Over voltage
- Cooling by free air convection
- 3" x 2" compact size
- LED indicator for power on
- No load power consumption <0.1W
- Operating altitude up to 4000 meters
- 3 years warranty

Specification

MODEL		SOH65-5	SOH65-12	SOH65-15	SOH65-24	SOH65-36	SOH65-48
INPUT	VOLTAGE RANGE	80 ~ 264VAC(refer to 'static characteristic')					
	FREQUENCY RANGE	47~63Hz					
	EFFICIENCY(Typ.)	84%	88%	89%	90%	90%	90%
	AC CURRENT(Typ.)	1.5A / 115VAC 1A / 230VAC					
	INRUSH CURRENT(Typ.)	30A/115VAC 60A/230VAC (cold start)					
	LEAKAGE CURRENT(max.)	Touch current< 100µA/240VAC					
OUTPUT	DC VOLTAGE	5V	12V	15V	24V	36V	48V
	RATED CURRENT	10A	5.42A	4.34A	2.71A	1.8A	1.36A
	CURRENT RANGE	0~11A	0~5.96A	0~4.77A	0~2.98A	0~1.8A	0~1.49A
	RATED POWER	50W	65W	65.1W	65W	64.8W	65.3W
	PEAK LOAD(10sec.)	55W	71.5W	71.6W	71.5W	71.5W	71.5W
	RIPPLE & NOISE (max.)	80mVp-p	100mVp-p	100mVp-p	120mVp-p	120mVp-p	120mVp-p
	VOLTAGE ADJ.RANGE	4.7-5.5V	11.4-13.2V	13.5-16.5V	22.8-27.6V	32.4-39.6V	45.6-52.8V
	VOLTAGE TOLERANCE	±2%	±2%	±2%	±1%	±1%	±1%
	LINE REGULATION	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	LOAD REGULATION	±2%	±1%	±1%	±1%	±1%	±1%
	SETUP, RISE TIME	500ms, 30ms / 230VAC 500ms, 30ms / 115VAC at full load					
HOLD UP TIME (Typ.)	30ms / 230VAC 12ms / 115VAC at full load						
PROTECTION	OVER LOAD	115 ~ 150% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed					
	OVER VOLTAGE	5.7-6.8V	13.8-16.2V	17.2-20.3V	28.4-32.4V	39.7-46.8V	55.2-64.8V
ENVIRONMENT	WORKING TEMP.	-20 ~ +70°C (Refer to "Derating Curve")					
	WORKING HUMIDITY	-20% ~ 90% RH non-condensing					
	STORAGE TEMP., HUMIDITY	-40 ~ +85°C , 10 ~ 95% RH non-condensing					
	TEMP. COEFFICIENT	±0.03% /°C(0 ~ 50°C)					
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes					
	OPERATING ALTITUDE	4000 meters					

Safety and electromagnetic compatibility	Safety standards	Refer to UL62368-1,TUV EN62368-1,CCC GB4943.1,EN60601-1(2XMOPP)		
	Withstand voltage and isolation resistance	I/P-O/P: 4KVac; 100MΩ / 500Vdc / 25°C / 70%RH		
	Electromagnetic	Parameter	Standard	Test Level / Note
		Conducted emission	BS EN/EN55032(CISPR32),FCC PART 15 / CISPR22 ,GB9254.1	Class B
		Radiated emission	BS EN/EN55032(CISPR32),FCC PART 15 / CISPR22 ,GB9254.1	Class B
		Harmonic current	BS EN/EN61000-3-2,GB17625.1	Class A
		Voltage flicker	BS EN/EN61000-3-3	----
		BS EN/EN55035		
		Parameter	Standard	Test Level /Note
		ESD	BS EN/EN61000-4-2	Level 4, 8KV air, Level 2, 4KV contact, criteria A
Electromagnetic compatibility immunity		RF field susceptibility	BS EN/EN61000-4-3	Level 3, criteria A
		EFT bursts	BS EN/EN61000-4-4	Level 3, criteria A
		Surge susceptibility	BS EN/EN61000-4-5	Level 3, 1KV/L-N, criteria A
		Conducted susceptibility	BS EN/EN61000-4-6	Level 3, criteria A
		Magnetic field immunity	BS EN/EN61000-4-8	Level 4, criteria A
		Voltage dips and interruptions	BS EN/EN61000-4-11	>95% dip 0.5 periods, 30% dip 25 periods , >95% interruptions 250 periods
OTHERS	MTBF	≥650Khrs MIL-HDBK-217F(25°C)		
	DIMENSION	PCB: 76.2*50.8*24mm(L*W*H)		
	PACKING	0.09Kg; 108pcs/10.7Kg/ 1CUFT		
NOTE	<p>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</p> <p>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12” twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.</p> <p>3. Tolerance: includes set up tolerance, line regulation and load regulation.</p> <p>4. Line regulation is measured from low line to high line at rated load.</p> <p>5. Load regulation is measured from 0% to 100% rated load</p> <p>6. Length of set up time is measured at cold first start, Turning ON/OFF the power supply very quickly may lead to increase of the set up time.</p> <p>7. The ambient temperature derating of 5°C/1000m is needed for operating altitude great than 2000m(6500ft).</p> <p>8. The power supply is considered a component which will be installed into a final equipment. All the EMC tests are been executed by mounting the unit on a 360mm*360mm metal plate with 1mm of thickness. The final equipment must be re-confirmed that it still meets EMC directives.</p> <p>9. Peak load 33% duty cycle maximum within every 30 seconds. Average output power should not be exceed the rated power.</p>			

Mechanical specification

Top View

Front View

NOTE:
Unit: mm
SVR1: Output adjustable resistor
TOL: ±1.00

AC Input Connector (CN1) : JST B3P-VH or equivalent

Pin No.	Assignment	Mating Housing	Termina
1	AC/N	JST VHR or equivalent	JST SVH-21T-P1.1 or equivalent
2	No Pin		
3	AC/L		

DC Output Connector (CN2) : JST B4P-VH or equivalent

Pin No.	Assignment	Mating Housing	Termina
1~2	+V	JST VHR or equivalent	JST SVH-21T-P1.1 or equivalent
3~4	-V		

Block diagram

